

VERIFICATION OF COMPLIANCE

No.: LVD SZES2209005345AT



Applicant: EcoFlow Inc.
Plant A202, Founder Technology Industrial Park, Shiyan Sub-district, Bao'an District, Shenzhen, 518000, Guangdong, China

Manufacturer: Same as applicant

Product Name: Portable Power Station

Product Description: --

Model No.: EFR600

Trade Mark:  

Rating: See Page 2

Protection against Electric Shock: Class I

Additional Information: --

Sufficient samples of the product have been tested and found to be in conformity with

Test Standard: EN IEC 62368-1:2020+A11:2020

as shown in the

Test Report Number(s): SZES220900534501

This Verification of Compliance has been granted to the applicant based on the results of tests, performed by Laboratory of SGS-CSTC Standards Technical Services Co., Ltd. on sample of the above-mentioned product in accordance with the provisions of the relevant harmonized standards under the Low Voltage Directive 2014/35/EU. The CE marking as shown below can be affixed, under the responsibility of the manufacturer, after completion of an EC Declaration of Conformity and compliance with all relevant EC Directives. The affixing of the CE marking presumes in addition that the conditions in annexes III and IV of the Directive are fulfilled.


Rocky Wang
Manager
SGS-CSTC



2022-11-29

This verification is issued by the company under its General Conditions of Services accessible at <https://www.sgs.com/en/terms-and-conditions>. Attention is drawn to the limitations of liability defined therein and in the Test Report here above mentioned which findings are reflected in this verification. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Member of SGS Group (Société Générale de Surveillance)




No.:

LVD SZES2209005345AT

Other information added:

Rating: AC Input: 200 - 240 V~, 50 Hz / 60 Hz, 8 A Max;
Solar / DC Input: 11 - 30 Vd.c., 8 A, 110 W Max;
Total Output: 484 W;
DC Output: 12,6Vd.c., 8A, 100W Max
AC Output (Bypass) (x1): 200 – 240V~, 600W (total), 50 Hz / 60 Hz
USB-A Output (x2): 5Vd.c., 2,4A, 12W Max per port
USB-C Input/Output (x1): 5 / 9 / 12 / 15 / 20 V d.c., 3A, 60W Max
Capacity: 256 Wh (20 Ah, 12,8 Vd.c.)
AC Output (x1): 230V~, 1,3A (total), 50 Hz / 60 Hz, 300W
Discharge temperature: -10°C-45°C, Charge Temperature: 0-45°C


Rocky Wang
Manager
SGS-CSTC



2022-11-29

This verification is issued by the company under its General Conditions of Services accessible at <https://www.sgs.com/en/terms-and-conditions>. Attention is drawn to the limitations of liability defined therein and in the Test Report here above mentioned which findings are reflected in this verification. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Member of SGS Group (Société Générale de Surveillance)