



Product Service

CERTIFICATE

No. Z2 090404 0013 Rev. 00

Holder of Certificate: **European Energy World S.L.**



European Energy World, S.L.

Calle Colón 1-23
46004 Valencia
SPAIN

Certification Mark:



Product: **Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**
Mono-Crystalline Silicon Photovoltaic Module

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 701262430602-00

Valid until: 2029-04-17

Date, 2025-01-22

CERTIFICATE

No. Z2 090404 0013 Rev. 00

Model(s):

MEPVxxxP(B)-15ZII (xxx=525-560 in step of 5W)
 MEPVxxxP(B)-13ZII (xxx=480-510 in step of 5W)
 MEPVxxxP(B)-11ZII (xxx=430-460 in step of 5W)
 MEPVxxxP(B)-8ZII (xxx=385-400 in step of 5W)
 MEPVxxxP(B)-17ZII (xxx=635-675 in step of 5W)
 MEPVxxxP(B)-16ZII (xxx=580-615 in step of 5W)
 MEPVxxxP(B)-14ZII (xxx=520-550 in step of 5W)
 MEPVxxxP(B)-12ZII (xxx=465-480 in step of 5W)
 MEPVxxxP(B)-18YII (xxx=530-550 in step of 5W)
 MEPVxxxP(B)-17YII (xxx=485-500 in step of 5W)
 MEPVxxxP(B)-16YII (xxx=445-455 in step of 5W)
 MEPVxxxP(B)-14YII (xxx=400-410 in step of 5W)
 MEPVxxxP(B)-12YII (xxx=355-365 in step of 5W)
 MEPVxxxP(B)-18XII (xxx=430-455 in step of 5W)
 MEPVxxxP(B)-17XII (xxx=395-415 in step of 5W)
 MEPVxxxP(B)-16XII (xxx=360-380 in step of 5W)
 MEPVxxxHH(B)-17ZII (xxx=675-700 in step of 5W)
 MEPVxxxHH(B)-16ZII (xxx=615-635 in step of 5W)
 MEPVxxxHH(B)-14ZII (xxx=555-570 in step of 5W)
 MEPVxxxHH(B)-12ZII (xxx=490-505 in step of 5W)
 MEPVxxxHH(B)-19YII (xxx=595-625 in step of 5W)
 MEPVxxxHH(B)-18YII (xxx=550-620 in step of 5W)
 MEPVxxxHH(B)-17YII (xxx=505-570 in step of 5W)
 MEPVxxxHH(B)-16YII (xxx=460-520 in step of 5W)
 MEPVxxxHH(B)-14YII (xxx=415-465 in step of 5W)
 MEPVxxxH(B)-17ZII (xxx=675-715 in step of 5W)
 MEPVxxxH(B)-16ZII (xxx=615-650 in step of 5W)
 MEPVxxxH(B)-14ZII (xxx=555-585 in step of 5W)
 MEPVxxxH(B)-12ZII (xxx=490-520 in step of 5W)
 MEPVxxxH(B)-18YII (xxx=550-580 in step of 5W)
 MEPVxxxH(B)-17YII (xxx=505-530 in step of 5W)
 MEPVxxxH(B)-16YII (xxx=460-480 in step of 5W)
 MEPVxxxH(B)-14YII (xxx=415-435 in step of 5W)

Black series:

MEPVxxxP-15ZII (xxx=525-560 in step of 5W)
 MEPVxxxP-13ZII (xxx=480-510 in step of 5W)
 MEPVxxxP-11ZII (xxx=430-460 in step of 5W)
 MEPVxxxP-8ZII (xxx=385-400 in step of 5W)
 MEPVxxxP-17ZII (xxx=635-675 in step of 5W)
 MEPVxxxP-16ZII (xxx=580-615 in step of 5W)
 MEPVxxxP-14ZII (xxx=520-550 in step of 5W)
 MEPVxxxP-12ZII (xxx=465-480 in step of 5W)
 MEPVxxxP-18YII (xxx=530-550 in step of 5W)
 MEPVxxxP-17YII (xxx=485-500 in step of 5W)
 MEPVxxxP-16YII (xxx=445-455 in step of 5W)
 MEPVxxxP-14YII (xxx=400-410 in step of 5W)
 MEPVxxxP-12YII (xxx=355-365 in step of 5W)
 MEPVxxxP-18XII (xxx=430-455 in step of 5W)
 MEPVxxxP-17XII (xxx=395-415 in step of 5W)
 MEPVxxxP-16XII (xxx=360-380 in step of 5W)
 MEPVxxxHH-17ZII (xxx=675-700 in step of 5W)
 MEPVxxxHH-16ZII (xxx=615-635 in step of 5W)
 MEPVxxxHH-14ZII (xxx=555-570 in step of 5W)
 MEPVxxxHH-12ZII (xxx=490-505 in step of 5W)
 MEPVxxxHH-19YII (xxx=595-625 in step of 5W)

CERTIFICATE

No. Z2 090404 0013 Rev. 00

MEPVxxxHH-18YII (xxx=550-620 in step of 5W)
MEPVxxxHH-17YII (xxx=505-570 in step of 5W)
MEPVxxxHH-16YII (xxx=460-520 in step of 5W)
MEPVxxxHH-14YII (xxx=415-465 in step of 5W)
MEPVxxxH(B)-17ZII (xxx=675-715 in step of 5W)
MEPVxxxH-16ZII (xxx=615-650 in step of 5W)
MEPVxxxH-14ZII (xxx=555-585 in step of 5W)
MEPVxxxH-12ZII (xxx=490-520 in step of 5W)
MEPVxxxH-18YII (xxx=550-580 in step of 5W)
MEPVxxxH-17YII (xxx=505-530 in step of 5W)
MEPVxxxH-16YII (xxx=460-480 in step of 5W)
MEPVxxxH-14YII (xxx=415-435 in step of 5W)
xxx is standing for rated output power at STC

Parameters:

Safety Class:	Class II
Max. System Voltage:	1500V DC
Construction:	Framed, with Junction box, cable and connector.
Fire Safety Class:	Class C according to UL790

Tested according to:

IEC 61215-1:2021
IEC 61215-1-1:2021
IEC 61215-2:2021
IEC 61730-1:2016
IEC 61730-2:2016